




# iMac Intel 21.5" EMC 2805 Blade SSD Replacement

Replace the SSD in your iMac Intel 21.5" EMC 2805.

Written By: Walter Galan



## INTRODUCTION

Use this guide to replace the Apple custom blade SSD (AHCI/PCIe x2).

**This guide is intended for the higher spec iMac Intel 21.5" EMC 2805 models that are equipped with an SSD.**



### TOOLS:

- [iMac Opening Tool](#) (1)
- [Phillips #0 Screwdriver](#) (1)
- [Plastic Cards](#) (1)
- [Tweezers](#) (1)
- [Spudger](#) (1)
- [T10 Torx Screwdriver](#) (1)
- [T8 Torx Screwdriver](#) (1)



### PARTS:

- [iMac Intel 21.5" \(2012-2017\) Adhesive Strips](#) (1)

## Step 1 — Display Assembly




**i** With the hinge free to move, the iMac will be unbalanced and hard to work on. Repairs are fast and easy with an [iMac service wedge](#), but can be completed without one.


- **Before beginning any work on your iMac:** Unplug the computer and press and hold the power button for ten seconds to discharge the power supply's capacitors.

**⚠** **Be very careful** not to touch the capacitor leads or any exposed solder joints on the back of the power supply. Only handle the board by the edges.

## Step 2



- Starting on the left of the display, near the power button, insert the iMac Opening Tool into the gap between the glass panel and the rear enclosure.

 The hub on the iMac Opening Tool will keep you from pushing the wheel in too far. If using a different tool, insert no more than 3/8" into the display. Otherwise, you risk severing antenna cables and causing serious damage.



## Step 3



- Use the tool like a pizza cutter—roll it along through the gap, and it will cut the foam adhesive through the center.
- ⓘ Be sure to always push with the handle behind the cutting wheel. If you pull, the wheel might get pulled out of the handle.
- Run the tool up along the left side of the display.

## Step 4



- Continue running the tool up around the top left corner.

## Step 5



- Cut the adhesive along the top left of the display.

## Step 6



- Continue along the top of the display.


**i** You may want to run the tool back and forth through what you've already cut a few times, to ensure you get as much of the adhesive separated as possible.

## Step 7



- Push the tool around the top right corner of the display.

## Step 8



- Wheel the tool down along the right side of the display.



## Step 9



- Finish pushing the opening tool to the bottom of the right side of the display.
- ❗ At this point, you'll want to run the tool back around the entire display, to ensure you cut as much adhesive as possible.

## Step 10



- ❗ While the opening tool cut most of the adhesive, the display will still be slightly adhered to the case. A plastic card will be necessary to free up the last of this adhesive.
- 📌 Set the iMac face-up on a table.
- Starting from the top right corner of the iMac, wedge a plastic card between the display and frame.
- ⚠ Be careful **not** to insert the plastic card more than 3/8", or you may damage internal components.

## Step 11



- Gently twist the plastic card sideways to create a gap between the display and frame.
- Move slowly and be careful not to stress the display glass too much—you only need to make a gap of about 1/4".

## Step 12




- Slide the card toward the center of the display to cut any of the remaining adhesive along the top right corner of the iMac.

 Be sure to **stop** before the iSight camera, or you may damage it.



## Step 13




- Wedge the plastic card into the top right corner once again, and leave it there to prevent the adhesive from resticking.

## Step 14



- Insert a second plastic card into the gap between the display and frame near the top left corner of the iMac.

## Step 15




- Gently twist the card upward, slightly increasing the space between the display and frame.
- ⓘ As with the other side, twist slowly to allow the adhesive time to separate, and be careful not to over-stress the display glass.

## Step 16



- Slide the plastic card toward the center, again stopping just before the iSight camera.

## Step 17



- Wedge the plastic card back into the top left corner.

## Step 18



- With both plastic cards inserted as shown near the corners, gently twist the cards sideways to increase the gap between display and case.
- ⓘ If there are any sections that seem to stick and won't separate, stop twisting and use one of the cards to cut the remaining adhesive.
- Begin to lift the top of the display up from the frame.
- ⚠ Only lift the display a few inches—the display data and power cables are still connected to the logic board.




## Step 19 — Display Assembly Cables



- Use a pair of tweezers to flip up the metal retaining bracket on the display data cable.
- Carefully pull the display data cable from its socket on the logic board.

⚠ Be sure to pull the display data cable connector straight out of its socket.

## Step 20



- While holding the display up with one hand, use the other hand to unplug the display power cable.
- ⓘ Lift the display up enough to have easy access to the connector, but not so much that you stretch the cables and stress their connections (about 8").

## Step 21 — Display



- Lift the display up to a near-vertical position.

**i** At this point there is still a strip of adhesive along the bottom of the display, that will hold the display to the frame like a hinge. You can loosen this adhesive by working the display up and down a few times.

## Step 22




**i** If necessary, a plastic card can be used to cut any remaining sections of the bottom adhesive strip.




## Step 23




- Lift the display up from the frame and remove it from the iMac.
- It may be necessary to slowly lift from one side, to peel against the remaining adhesive.

 Be very careful handling the display—it's big, heavy, and made of glass.


## Step 24 — Lower Support Bracket



- Remove the following five Phillips screws holding the lower support bracket in place:
  - Four 3.2 mm screws
  - One 1.7 mm screw


 You may need to peel up the display adhesive lining the bottom edge of the iMac enclosure to access the screws.

## Step 25




- Remove the lower support bracket from the iMac enclosure.

## Step 26 — Right Speaker



- Use the tip of a spudger to push on either side of the right speaker cable connector to *walk* it out of its socket on the logic board.


## Step 27



- Remove the two 10.0 mm T10 screws securing the right speaker to the rear enclosure.



## Step 28



- Insert the tip of a spudger between the right speaker and the antenna cable that is routed into the speaker's right side.
  - Run the spudger down along the right side of the speaker to pry the antenna cable from its channel in the right speaker.
- ⓘ If the channel is not easily accessible, you can pull the speaker gently away from the case to gain access to the antenna cable.

## Step 29



- Lift the right speaker straight up and remove it from the iMac.

**i** It may be helpful to tip the top of the speaker away from the rear enclosure when removing it from the iMac.


## Step 30 — Hard Drive Brackets



- Remove the following screws securing the hard drive bracket to the rear enclosure:
  - Two 21 mm T10 Torx screws from the left-hand hard drive bracket.
  - One 9 mm T10 Torx screw.
  - One 27 mm T10 Torx screw.





## Step 31



- Remove the left and right hard drive brackets from the iMac.

## Step 32 — Power Supply





 The next few steps bring your hands close to the exposed face of the power supply. **Do not** touch the face of the power supply or any of the exposed solder. Touching it risks a high voltage shock from the many large capacitors attached to the board.

- Use the tip of a spudger to push each side of the power button cable connector and gently *walk* it out of its socket.




## Step 33



- Use the tip of a spudger to push each side of the power supply control cable connector and gently *walk* it out of its socket.

## Step 34



- Remove the two 7.2 mm T10 Torx screws securing the power supply to the rear enclosure.
- ⓘ In newer model iMacs these are 7.2 mm T8 or T9 Torx screws.

## Step 35



⚠ When working on the power supply, **be very careful** not to touch the capacitor leads or any exposed solder joints on the back of the power supply. Only handle the board by the edges.

- Tilt the power supply forward.

## Step 36



- Pull the power supply slightly up and out from the rear enclosure.
- Rotate the power supply counterclockwise, lifting the right side up about an inch higher than the left.




## Step 37



- Slide the power supply to the right to clear the screw posts on the rear enclosure.


## Step 38



- Rock the power supply forward and remove it from its recess in the rear enclosure.

**⚠ Do not** try to completely remove the power supply from the iMac yet—it is still connected to the logic board.

## Step 39




**⚠ Be very careful** not to touch the capacitor leads or any exposed solder joints on the back of the power supply. Only handle the board by the edges.

**i** Flip the power supply over to access the DC power cable connection behind the logic board.

- Squeeze the tab on the back side of the DC power cable connector and pull it straight out of its socket on the back of the logic board.




## Step 40





- i** You may find it helpful to set the iMac down on its back for the next couple of steps.
- Use the flat end of a spudger to press the clip on the side of the AC inlet cable connector inward.
  - While pressing on the release clip with the spudger, grasp the AC inlet cable, and pull the connector straight out of its socket.

## Step 41



- Remove the power supply from the iMac.

## Step 42 — Fan



- Use the tip of a spudger to push the fan cable connector out of its socket on the logic board.
- ⓘ It is recommended to carefully push on both sides of the connector to *walk* it out of its socket.


## Step 43



- Remove the following screws securing the fan to the rear enclosure:
  - Two 12.5 mm T10 screws
  - One 9.9 mm T10 screw



## Step 44



- Lift and remove the fan from the iMac.

## Step 45 — Hard Drive Assembly





- Lift the hard drive from the edge nearest the logic board and pull it slightly out of its recess.



The hard drive is attached by a single SATA power/data cable—do **not** attempt to fully remove it from the iMac yet.



## Step 46




- Use a spudger to disconnect the single SATA power and data combo cable by gently prying its large plastic connector away from the hard drive.

## Step 47



- Remove the hard drive assembly from the iMac.

## Step 48 — Hard Drive Tray



- Remove the single 7.2 mm T10 screw securing the hard drive tray to the rear enclosure.


## Step 49



- Remove the hard drive tray from the rear enclosure.




## Step 50 — Logic Board Assembly



- Use the tip of a spudger to *walk* the left speaker cable connector out of its socket.
- i** It is recommended to first press on one side of the connector, then press on the other side until freed.


## Step 51



- De-route the left speaker cable by pulling it straight up out of the retaining clip in the back of the rear enclosure.




## Step 52



- In a similar fashion as the previous step, de-route the combo SATA data/power cable up out of the retaining clip.


## Step 53




- Use a pair of tweezers to flip up the metal retaining bracket on the iSight camera cable connector.
- Pull the iSight camera cable straight out of its socket on the logic board.


 **This is a delicate connector that can be easily damaged.**


## Step 54



-  If necessary, use the tip of a spudger to peel back the tabs covering the antenna connectors.

## Step 55




- Use the tip of a spudger to disconnect each of the four antenna connectors from the AirPort/Bluetooth card.
-  Note the original positions for each connector when reconnecting the cables.




## Step 56



- Use the flat edge of a spudger to pry the headphone jack cable connector from its socket on the logic board.

 Push the cable slightly to the right.


## Step 57



- Remove the following screws securing the exhaust duct to the rear enclosure:
  - Two 6.3 mm T8 screws
  - Two 4.7 mm T8 screws



## Step 58





- Remove the four 7.2 mm T10 screws securing the logic board to the rear enclosure.

## Step 59




- Use a pair of tweezers to peel the tape covering the exhaust duct.

## Step 60



- Tilt the top of the logic board away from the rear enclosure.

## Step 61



- Lift the logic board straight up and out of the iMac.

⚠ Be careful not to snag the board on any of the rear case's screw posts.

ⓘ The I/O inputs at the bottom of the logic board will be the greatest challenge. It is recommended to pull gently to avoid any damage.






## Step 62 — Blade SSD



- Remove the T9 Torx screw securing the SSD to the logic board.

## Step 63



- Slightly lift the rightmost side of the SSD and firmly slide it straight out of its socket on the logic board.

To reassemble your device, follow these instructions in reverse and use our [Adhesive Strips Guide](#) to reattach the display glass.

This document was last generated on 2017-12-01 12:11:24 PM.